



Specifications:

content: 100% Polyurethane
 backing: 70% Polyester; 30% Cotton
 finish: Antimicrobial – Silver Ion Technology
 Repeat: n/a
 weight: 20.3 oz. / lin. yd. (630g/M)
 width: 54 inches

Flammability Passes:

California Tech. Bulletin #117-2013
 UFAC Class 1
 NFPA 260 Class 1
 MVSS 302
 IMO A. 652 (16) 8.2

Performance:

abrasion: Heavy Duty – Exceeds 200,000 cycles
 (Wyzenbeek – Cotton duck Abradant) (ASTM D4157)
 light fastness: Class 4/100 hrs. min. (AATCC16A)
 color fastness: Class 5 (ASTM D3597, AATCC 8) Wet
 Class 5 (ASTM D3597, AATCC 8) Dry
 physical properties: Class 5 (ASTM D3511) Brush Pill
 130 lbs. warp, 120 lbs. weft (ASTM D4034) Breaking Strength
 61 lbs. warp, 81 lbs. weft (ASTM D4034) Seam Slippage
 50,000 cycles (CFFA 10) Flex Resistance
 Pass (CFFA 6a) Cold Crack
 Pass (ISO 1419) 5 weeks
 environmental benefits: PVC free
 Phthalate – compliant CPSC sec. 108
 Lead – compliant CPSC sec. 101
 made in: China

Care & Cleanability:

A clean cloth, dampened with the appropriate cleaning solution, should be applied to the affected areas as soon as possible. Blot the fabric with the treated cloth, working from the outer edge of the stained area and moving in toward the center. In order to effectively draw out the stain, renew the cleaning cloth as often as necessary to maintain an absorbent surface.

Clean all stained areas as soon as possible in accordance with the recommended stain removal procedures. Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Hot water extraction or steam cleaning is not a recommended cleaning method. Clean spots or stains from the outside to the middle of the affected area to prevent circling (see Stain Removal Matrix below).

1. Soap and water
2. Difficult stains use Fantastik® or Formula 409®
3. Disinfects with 5:1 water / bleach solution